



## SecuraSpan™ Horizontal Lifeline System Modular Multi-Base Design

### Description:

The SecuraSpan™ System is engineered to provide personnel with continuous fall protection, horizontal mobility and freedom of movement. A typical system would include at least two SecuraSpan™ stanchions (single-span up to 60 ft) and cable lifeline assembly with Zorbit™ energy absorber. Longer multi-span systems are available with additional stanchions and bypass brackets.

### Features & Benefits:

- Maximum Jobsite Versatility
  - Interchangeable bases maximize investment and increase versatility in the field
  - Single and multi-span systems offer length and jobsite clearance flexibility
- Maximum Worker Safety
  - Rigorously tested and expert engineered system replaces unsafe home-made types
  - Integrated Zorbit™ energy absorber maintains safe fall clearance and impact forces
- Maximum Worker Productivity
  - Lightweight and portable design for easy handling, installation and storage
  - Pass-through design for 100% tie-off and complete freedom of movement

### Component Models:

- 7400045:** SecuraSpan™ Loop Rebar Stanchion and Base
- 7400047:** SecuraSpan™ I-Beam Stanchion and Base
- 7400215:** SecuraSpan™ Rebar Stanchion and Base
- 7400214:** Rebar Tie-Back Base (*for use with 7400215*)

### System Models:

Complete configured system kits available.

### General Specifications:

**Stanchion & Base:** Carbon steel, zinc plated finish

**Beam/Rebar Sizes:** I-beam base fits flanges 6" to 12" wide and 2-1/4" thick. Rebar/Shear stud base fits 1/2" to 1" dia., 4" to 12" center to center. Rebar loop base fits 1/2" to 4 1/2" dia., 3" or greater spacing, 3-1/2" to 8" high.

**Capacity:** 310 lbs

**Weight:** 7400045 = 52 lbs., 7400047 = 36 lbs., 7400215 = 38 lbs., 7400214 = 11 lbs.

**Height of installed stanchion:** 36"

**Minimum Breaking Strength:** 5,000 lbs

**Standards:** Meets OSHA 1910.66, 1926.502

### Capital Safety

USA : 800.328.6146 • Canada : 800.387.7484 • Latin America: +1 651.385.4301 • Asia : +65 6558 7758  
Australia: 1800 245 002 • New Zealand: 0800 212 505 • Europe, Middle East, Africa : +33 (0)4 97 10 00 10  
Northern Europe : +44 (0) 1928 571324 • Germany: +49 2634 8052

[www.capitalsafety.com](http://www.capitalsafety.com) • [info@capitalsafety.com](mailto:info@capitalsafety.com)

**ISO 9001  
REGISTERED**

©2009, Capital Safety